


## SAFETY DATA SHEET

### ADH1610 100% Isopropyl Alcohol Wipe

Page 1 of 6  
Dated 11/10/2018

This Safety Data Sheet contains information concerning the potential risks to those involved in handling, transporting and working with the material, as well as describing potential risks to the consumer and the environment. This information must be made available to those who may come into contact with the material or are responsible for the use of the material. This Safety Data Sheet is prepared in accordance with formatting described in the REACH Regulation (EC) No 1907/2006, and described in CLP Regulation (EC) No 1272/2008.

<b>SECTION 1: Identification of the substance/mixture and the company/undertaking</b>	
<b>1.1. Product Identifier</b>	
<b>Product Name</b>	Adhere ADH1610 100% Isopropyl Alcohol Wipe
<b>1.2. Relevant identified uses of the substance or mixture and uses advised against</b>	
Intended use	Surface cleaning and disinfection
<b>1.3. Details of the supplier of the safety data sheet</b>	
Name	Intertronics
Full address	17 Station Field Industrial Estate Banbury Road Kidlington, Oxfordshire OX5 1JD England
Email address of the competent person responsible for the Safety Data Sheet	msds@intertronics.co.uk
<b>1.4. Emergency telephone number</b>	
For urgent enquiries refer to	+44 1865 842842

<b>SECTION 2: Hazards identification</b>	
<b>2.1. Classification of the substance or mixture</b>	
<b>Classification in accordance with the Classification Labelling and Packaging Regulation EC (no) 1272/2008:</b>	
Flam. Liq. 2 H225	Highly flammable liquid and vapour
Eye Irrit. 2 H319	Causes serious eye irritation
STOT SE 3: H336	May cause drowsiness or dizziness
<b>2.2. Label elements</b>	
<b>Labelling in accordance with the Classification Labelling and Packaging Regulation EC (no) 1272/2008</b>	
Signal words:	Danger
Hazard pictograms:	
Hazard statements:	H225: Highly flammable liquid and vapour H319: Causes serious eye irritation H336: May cause drowsiness or dizziness P261: Avoid breathing dust/fume/gas/mist/vapours/spray. P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention.

### 2.3. Other hazards

In confined spaces, vapours may build up to form flammable vapour/air mixtures.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable – product is a mixture

### 3.2. Mixtures

Isopropanol impregnated onto a paper tissue

Name	CAS or EC No	Concentration	Classification
Propan-2-ol (Isopropanol)	CAS 67-63-0 EC 200-661-7 Reg. No. 01-2119457558- 25-0000	100%	Flam. Liq. 2 H225 Eye Irrit. 2 H319 STOT SE 3 H336 <i>In accordance with CLP 1272/2008</i>

See section 16 for full description of H statements.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>Eye contact:</b>	Wash thoroughly with water for several minutes and obtain medical attention if signs of discomfort.
<b>Inhalation:</b>	Remove from exposure. If breathing becomes difficult call a doctor.
<b>Skin contact:</b>	Wash off with soap and water.
<b>Ingestion:</b>	If swallowed, rinse mouth with water.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>Eye contact:</b>	If liquid from the wipe gets into the eye it may cause redness, stinging, watering of the eye.
<b>Inhalation:</b>	Symptoms unlikely from use of small numbers of wipes, but inhalation of large amounts may cause headaches, dizziness, unconsciousness.
<b>Skin contact:</b>	Prolonged skin contact may cause drying of the skin.
<b>Ingestion:</b>	Ingestion of the liquid may cause irritation to the mouth and throat, and symptoms similar to inhalation.

### 4.3. Indication of any immediate medical attention and special treatments needed

Symptomatic treatment as required.

SECTION 5: Firefighting measures	
<b>5.1. Extinguishing media</b>	Water spray, alcohol resistant foam, dry powder and carbon dioxide extinguishers are suitable.
<b>5.2. Special hazards arising from the substance or mixture</b>	No special hazards.
<b>5.3. Advice for firefighters</b>	Fire fighters should wear protective clothing and breathing apparatus as appropriate.

SECTION 6: Accidental release measures	
<b>6.1. Personal precautions, protective equipment and emergency procedures</b>	Exclude unnecessary personnel. Open doors and windows to ensure good ventilation. Eliminate ignition sources.
<b>6.2. Environmental precautions</b>	Prevent entry into sewers and watercourses.
<b>6.3. Methods and material for containment and cleaning up</b>	Collect wipes and place in a sealable container for disposal.
<b>6.4. Reference to other sections</b>	See section 8 and 13 for further advice.

SECTION 7: Handling and storage	
<b>7.1. Precautions for safe handling</b>	Ensure adequate ventilation. Avoid contact with eyes and prolonged contact with skin. Keep away from sources of ignition.
<b>7.2. Conditions for safe storage, including any incompatibilities</b>	Store in its original labelled container in a cool, well ventilated area, away from heat, sparks and other sources of ignition. Keep out of reach of children and animals.
<b>7.3. Specific end use(s)</b>	No special precautions.

SECTION 8: Exposure controls/personal protection			
<b>8.1. Control parameters</b>			
Workplace exposure limits:			
Substance	8 hour exposure limit	15 minute exposure limit	Source, Type
Isopropanol	400 ppm (999 mg/m <sup>3</sup> )	500 ppm (1250 mg/m <sup>3</sup> )	EH40 2011
<b>DNELS:</b>			
DNELS			
	Worker	General Population	
	Chronic Effects	Chronic Effects	
Human Oral		26 mg/kg	
Human Dermal	888 mg/kg/day	319 mg/kg	
Human Inhalation	500 mg/m <sup>3</sup>	89 mg/m <sup>3</sup>	

**PNECS:**

PNEC Aqua (Freshwater)	140.9 mg/l
PNEC Aqua (Marine Water)	140.9 mg/l
PNEC Sediment	552 mg/kg
PNEC Soil	28 mg/kg

**8.2. Exposure controls**

Engineering measures: Normal room ventilation is expected to be adequate. If large numbers of wipes are being used in an enclosed space then additional local exhaust ventilation may be required.

Respiratory protection: Not normally required

Hand protection: If large numbers of wipes or prolonged contact is expected, then suitable gloves may be required. Butyl rubber, nitrile rubber, Viton (fluoroelastomer) may be suitable, but glove manufacturers recommendations should always be checked.

Eye protection: If large numbers of wipes are being used, then safety glasses or goggles may be appropriate.

Skin protection: If large numbers of wipes or prolonged contact is expected, then suitable protective clothing should be worn. Remove protective clothing when contaminated and wash before reuse.

Environmental Exposure Controls: Not normally required.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Appearance:	Clear liquid absorbed onto towelling
Odour:	Alcoholic odour
Odour threshold:	Approximately 22 ppm (propan-2-ol)
pH:	Approximately neutral
Boiling point / range:	82°C at 1013 hPa (propan-2-ol)
Melting point / range °C:	-89°C (propan-2-ol)
Flash point °C:	Approx. 18°C (70% propan-2-ol)
Evaporation rate:	1.7 (n-Butyl Acetate=1) (propan-2-ol)
Flammability:	Flammable
Upper/lower flammability limits:	2-12% (propan-2-ol)
Vapour pressure:	42 hPa at 20°C (propan-2-ol)
Vapour density:	2.07 (Air=1) (propan-2-ol)
Relative density:	0.7855 g/cm <sup>3</sup> at 20°C (propan-2-ol)
Solubility in water:	Completely miscible
Solubility in other solvents:	Miscible with diethyl ether and ethanol
Partition coefficient (log K <sub>ow</sub> ):	0.05 at 25°C (propan-2-ol)
Autoignition temperature:	> 399°C (propan-2-ol)
Decomposition temperature:	No decomposition when used under normal conditions
Viscosity:	2.5 mPas at 20°C (propan-2-ol)
Explosive properties:	Not classified as explosive
Oxidising properties:	Not classified as oxidising

**9.2. Other information**

None

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Not considered to be reactive.

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

None expected.

**10.4. Conditions to avoid**

Avoid exposure to high and freezing temperatures.

**10.5. Incompatible materials**

Avoid contact with strong oxidisers.

**10.6. Hazardous decomposition products**

None known.

**SECTION 11: Toxicological information****11.1. Information on toxicological effects**

This product has not been tested. Judgements on the expected toxicity of this product have been made based upon consideration of its major components.

- |                                    |   |
|------------------------------------|---|
| (a) acute toxicity                 | Not expected to present an acute toxicity hazard<br>LD50 (oral, rat) >2000 mg/kg (propan-2-ol)<br>LD50 (dermal, rabbit) >2000 mg/kg (propan-2-ol)                   |
| (b) skin corrosion/irritation      | Not expected to be irritating to skin. Prolonged and frequent exposure may dry the skin.<br>Rabbit, dermal: not irritating (propan-2-ol)                            |
| (c) serious eye damage/irritation  | If liquid from the wipe gets into the eye it may cause irritation<br>Rabbit, eye: irritating (propan-2-ol)  |
| (d) respiratory/skin sensitization | Not expected to be sensitising<br>Guinea pig, Buehler test: Not sensitising (propan-2-ol)   |
| (e) germ cell mutagenicity         | Not expected to be mutagenic<br>Ames test, Salmonella typhimurium (with and without metabolic activation): not mutagenic (propan-2-ol)                              |
| (f) carcinogenicity                | Not expected to be carcinogenic<br>Rat (inhalation, 2 years): NOEL 5000 ppm   |
| (g) reproductive toxicity          | Not expected to be reprotoxic. Animal studies for propan-2-ol gave no indication of a developmental toxic effect at doses that were not toxic to the parent animals |
| (h) STOT-single exposure           | Inhalation of vapours may cause drowsiness and dizziness  |
| (i) STOT-repeated exposure         | NOAEL 5000 ppm propan-2-ol  |
| (j) aspiration hazard              | Not expected to present an aspiration hazard.   |

**SECTION 12: Ecological information****12.1. Toxicity**

Not expected to be toxic to the environment

Toxicity to fish: LC50: > 100 mg/l, 48 h, *Leuciscus idus melanotus*, static

Toxicity to invertebrates: EC50: > 100 mg/l, 48 h, *Daphnia magna*, static

Toxicity to algae : EC50: > 100 mg/l, 72 h, *Scenedesmus subspicatus*, static

**12.2. Persistence and degradability**

Propan-2-ol is readily biodegradable. The tissue component is expected to biodegrade in the environment.

**12.3. Bioaccumulative potential**

Propan-2-ol is readily metabolised and is not expected to bioaccumulate.

**12.4. Mobility in soil**

Propan-2-ol will quickly evaporate and is expected to partition into the air compartment.

**12.5. Results of PBT and vPvB assessment**

Propan-2-ol is not considered to be PBT or vpvB.

**12.6. Other adverse effects**

None known

**SECTION 13: Disposal considerations****13.1. Waste treatment methods**

Wastes should be disposed of in accordance with local regulations.

Unused product may be disposed of by incineration.

For used product, consideration should be given to any contaminants before deciding on the disposal method.

**SECTION 14: Transport information**

This product does not need to be transported as dangerous goods, in accordance with UN 3175 Special Provision 216 (ADR/RID/IMDG) and Special Provision A46 (IATA).

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

All components are listed as existing substances in Europe

**15.2. Chemical Safety Assessment**

A Chemical Safety Assessment has not been carried out for this product. A Chemical Safety Assessment has been carried out for the main component, propan-2-ol.

**SECTION 16: Other information****Revision information:**

SDS reviewed – no significant changes

**List of Abbreviations used in this SDS:**

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging Regulation (EC) no 1272/2008

DSD Dangerous Substances Directive 67/548/EEC

DPD Dangerous Preparations Directive 1999/45/EC

EC European Community/Commission

PBT Persistent, Bioaccumulative and Toxic

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) no 1907/2006

vPvB very Persistent, very Bioaccumulative

**References:**

CLP Regulation 1272/2008

ECHA Chem database of registered substances

Suppliers SDS

**Method used for classification of mixtures:**

Ingredient based approaches

**H Statements used in Section 3**

H225 Highly flammable liquid and vapour

H319 Causes serious eye irritation

H336 May cause drowsiness or dizziness

**Training requirements for workers**

No special training requirements.